



SE220HDZ (Metric Units)

High-Duty All-Electric

CLAMP SPECIFICATIONS

Clamping force	tonf	220			
Distance between tie-bars	mm	610 x 560			
Overall size of platens (H x V)	mm	880 x 830			
Open daylight (max.)	mm	1130			
Mold space (min.-max.)	mm	300 – 580			
Opening stroke (max.)	mm	550			
Mold open/close speed (max.)	mm/sec	1300			
Locating ring diameter	mm	101.6			
Ejector pattern		Center, 178mm, 406mm (13 points)			
Ejector stroke	mm	150			
Ejector force	tonf	6.0			

INJECTION SPECIFICATIONS

Plasticizing unit		C750M		C1100L	
		mm	kgf/cm ²	mm	kgf/cm ²
Screw diameter	mm	45	2200	50	2210
Injection pressure	kgf/cm ²	45	1780	50	1760
Holding pressure	kgf/cm ²	45	1780	50	1760
Injection capacity	cm ³	329	406	501	628
Injection weight (GPPS)	g	316	390	481	603
	oz	11.2	13.8	17.0	21.4
Plasticizing capacity (max.)	kg/hr	98	134	151	192
Screw speed (max.)	rpm	250	250	250	250
Heater capacity (6 zones)	KW	12.8	13.9	21.5	23.4
Injection rate (max.)	cm ³ /sec	254	314	314	394
Injection speed (max.)	mm/sec	160		160	
Screw stroke	mm	207		255	
Nozzle contact force	kgf	6000		6000	
Injection unit stroke (penetration)	mm	430 (65)		450 (65)	
Hopper capacity	liter	50		100	

MACHINE SPECIFICATIONS

Main breaker capacity	amps	200 @ 230V	
Machine dimensions (L x W x H)	mm	6436 x 1580 x 2065	6436 x 1580 x 2254
Machine weight	tonf	10.1	10.9

NOTE: Specifications subject to change without notice. Machine series photo at top may be different model size.